**DUPLEX SILICONE SPRAY 400ML** 

Page: 1

Compilation date: 24/06/2015

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: DUPLEX SILICONE SPRAY 400ML

Product code: SPA02785

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

# 1.3. Details of the supplier of the safety data sheet

Company name: Duplex Cleaning Machines (UK) Ltd

Unit 27 Joseph Wilson Industrial Estate

Millstrood Road

Whitstable

Kent

CT5 3PS

**England** 

Tel: +44 (0)1227 771276

Fax: +44 (0)1227 770220

Email: info@duplex-cleaning.com

# 1.4. Emergency telephone number

Emergency tel: +44 (0)1227 771276

(office hours only)

## Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Aerosol 1: H222; -:

H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Harmful to aquatic life with long

lasting effects.

#### 2.2. Label elements

### Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

[cont...]



**DUPLEX SILICONE SPRAY 400ML** 

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS08: Health hazard
GHS07: Exclamation mark







Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P332+313: If skin irritation occurs: Get medical advice/attention.

P331: Do NOT induce vomiting.

P362: Take off contaminated clothing.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture. SOLVENT ABUSE CAN KILL

INSTANTLY

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

[cont...]

**DUPLEX SILICONE SPRAY 400ML** 

Page: 3

### **Hazardous ingredients:**

### PETROLEUM GASES, LIQUEFIED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	-	Flam. Gas 1: H220; Press. Gas: H280	50-70%

### LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

265-151-9	64742-49-0	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224;	10-30%
			Skin Irrit. 2: H315; Aquatic Chronic 2:	
			H411	

### Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

# 4.3. Indication of any immediate medical attention and special treatment needed

# Section 5: Fire-fighting measures

# 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

**DUPLEX SILICONE SPRAY 400ML** 

Page: 4

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

# 7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

### Hazardous ingredients:

# PETROLEUM GASES, LIQUEFIED

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1750mg/m3	2180mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

**Respiratory protection:** Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

[cont...]

**DUPLEX SILICONE SPRAY 400ML** 

Page: 5

# 9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic of organic solvents

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Acetone.

Viscosity: Non-viscous

**Boiling point/range°C:** <=35 **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: <23 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: Not applicable. pH: Not applicable.

VOC g/I: No data available.

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

# 10.1. Reactivity

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

## Hazardous ingredients:

**DUPLEX SILICONE SPRAY 400ML** 

Page: 6

### PETROLEUM GASES, LIQUEFIED

GASES	RAT	4H LC50	> 20	ma/l
0,1020	1011		,0	9/.

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** Absorption through the lungs can occur causing symptoms similar to those of ingestion.

### **Section 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity values: No data available.

# 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

**DUPLEX SILICONE SPRAY 400ML** 

Page: 7

### **Section 14: Transport information**

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D Transport category: 2

### **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

### **Section 16: Other information**

## Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H224: Extremely flammable liquid and vapour. H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.